

US009661593B2

(12) United States Patent Dick et al.

(10) Patent No.: US 9,661,593 B2 (45) Date of Patent: May 23, 2017

(54) POWER CONTROL FOR COMMUNICATIONS SYSTEMS UTILIZING HIGH SPEED SHARED CHANNELS

(71) Applicant: **InterDigital Technology Corporation**, Wilmington, DE (US)

(72) Inventors: **Stephen G. Dick**, Nesconset, NY (US); **Marian Rudolf**, Montreal (CA)

(73) Assignee: **InterDigital Technology Corporation**, Wilmington, DE (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 73 days.

(21) Appl. No.: 14/658,398

(22) Filed: Mar. 16, 2015

(65) **Prior Publication Data**US 2015/0189607 A1 Jul. 2, 2015

Related U.S. Application Data

- (63) Continuation of application No. 14/249,104, filed on Apr. 9, 2014, now Pat. No. 8,983,524, which is a (Continued)
- (51) Int. Cl. H04W 52/54 (2009.01) H04W 52/12 (2009.01) (Continued)
- (58) Field of Classification Search
 CPC ... H04W 52/54; H04W 52/221; H04W 52/22;
 H04W 72/0406; H04L 1/16; H04L 1/1607
 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

5,696,766 A 5,715,521 A 12/1997 Yeung et al. 2/1998 Fukasawa et al. (Continued)

FOREIGN PATENT DOCUMENTS

EP 1 017 187 A2 7/2000 EP 1 039 657 A1 9/2000 (Continued)

OTHER PUBLICATIONS

Telecommunications Industry Association, "TIA/EIA Interim Standard, Mobile Station-Base Station Compatibility Standard for Dual-Mode Wideband Spread Spectrum Cellular System, TIA/EIA/IS-95-A (Revision of TIA/EIA/IS-95)," (May 1995). (Due to the size of this document, it is submitted in 3 parts.)

(Continued)

Primary Examiner — Warner Wong (74) Attorney, Agent, or Firm — Volpe and Koenig, P.C.

(57) ABSTRACT

A method and apparatus are described for controlling transmitter power in a wireless communication system in which both dedicated and shared channels are utilized. A wireless transmit/receive unit (WTRU) may receive a first channel (e.g., downlink shared channel), power commands for a second channel (e.g., dedicated channel) and power commands for a third channel (e.g., uplink shared channel). The WTRU may transmit in a transmission time interval at least one of the second channel and the third channel. Acknowledgments and negative acknowledgements to signals received over the first channel may be sent on the third channel. The WTRU may determine a transmission power level of the second channel in response to the second channel power commands and not the third channel power commands. The WTRU may determine a transmission power level of the third channel in response to the third channel power commands and not the second channel power commands.

24 Claims, 6 Drawing Sheets

